



Allante FRee[®]



Coated Fabric Upholstery Solutions

Allante FRee®



AF-905
Province Blue



AF-901
Bright White



AF-917
White Crush



AF-922
Ivory



AF-937
Golden Kiwi



AF-941
Desert Sun



AF-940
Blooming Dahlia



AF-912
Sierra Brick



AF-942
Ginger Spice



AF-925
Italian Rose



AF-916
Red Truffle



AF-944
Thais Red



AF-924
Purple Impulse



AF-921
Chocolate Sundae



AF-904
Garden Green



AF-933
Mystic Lilly



AF-910
Illusion



AF-939
Birch




AF-907
Bleached Sand



AF-911
Taupe Fawn




AF-934
Winter Green



AF-914
Oasis Green



AF-935
Pagoda



AF-926
Niagara Mist



AF-913
Warm Smoke



AF-938
Mist



AF-915
Cookie



AF-945
Flannel



AF-931
Hawaiian Surf



AF-930
Regatta



AF-929
Nautical Blue



AF-936
Lagoon



AF-909
Autumn Rain



AF-946
Elephant



AF-903
Gibraltar



AF-943
Granite



AF-928
Horizon



AF-923
Mountain Sky




AF-908
Old Navy




AF-920
Galaxy



AF-902
Ice




AF-945
Malibu Blue



AF-927
Riverside



AF-919
Eclipse



AF-906
Chateau Grey



AF-918
Ink Black



Allante FFree[®]

Specifications

Roll Width: 54 inches
 Roll Length: 40 yards
 Weight: 29.3 ± 2 oz per linear yard
 Thickness: 45 ± 5 mils
 Cold Crack: -25°
 200 Hours WeatherOmeter

Abrasion Resistance:

Wyzenbeek test method: #10 Cotton Duck;
 250,000 Cycles Pass: No significant wear.

Features & Benefits

- Flame Retardant Additive Free
- Anti-Microbial Retardant Additive Free
- Formulated Phthalate Free
- Denim Dye Resistant
- Oil Resistant
- Cleanable
- Made in North America
- Bromine-free, No Halogenated Flame Retardants (HFRs)
- REACH compliant
- RoHS compliant
- No heavy metals
- No Mercury
- No Bisphenol A (BPA)
- No Ozone Depleting Chemicals
- No PBT's (Persistent Bio-accumulative Toxic Chemicals)
- Contains bio-based renewable ingredients

Content

Vinyl

Backing

100% Polyester

Flame Resistance

Manufactured to meet the following flammability* requirements:

- EN 1021-1 and 2
- Cal TB 117-2013 (Section 1-Cover Fabric)
- UFAC Class 1
- AB2998, NY SB S4630B
- Compliance NFP 260

*This term and corresponding data refer to the typical performance in the specific test indicated. They should not be construed to imply the behavior of this or any other material under actual fire conditions.

Recommended Applications

- Corporate
- Public Spaces
- Hotel/Motel/Entertainment
- Restaurant
- General Upholstery
- Residential/Home Office
- RV
- Casino
- Marine Interior

Care and Cleaning Instructions

This product has been developed to emulate the look and feel of soft leather. The unique super dull finish is designed to be low burnishing, non-polishing and resistant to ultraviolet exposure.

Our vinyls have superb tailoring qualities, which make pre-heating and steaming unnecessary and are not recommended in the fabrication process.

Because of the special leather-like finish, additional precautions should be observed when processing and cleaning. Please avoid contact with marking inks, glues and other staining materials that may damage vinyl during manufacturing. Protecting seating with a clean polyethylene cover, as is common in the automotive industry, should enable you to deliver a stain-free unit to the customer.

If, despite all precautions, staining material does come in contact with our vinyls, cleaning should be immediate and should follow these instructions:

- Dry soil, Dust and Dirt, Dried on Dirt: Remove with soft cloth dampened with water.
- Variation in Surface Gloss: Wipe with a soft cloth dampened with water. Allow to air dry.
- Stubborn Dirt: Wash with a soft cloth moistened with a mild soap and water. Rinse with clean water.
- Stubborn Spots and Stains: Spray with either Formula 409®, or CRC 40173 Tannery Leather, Vinyl & More Cleaner & Conditioner, wiping with a soft cloth. Rinse with clean water.
- Liquid Spills: Wipe immediately with a clean absorbent cloth. Rinse with clean water.
- Food, Grease, and Oily Stains: Spray immediately using either Formula 409®, or CRC 40173 Tannery Leather, Vinyl & More Cleaner & Conditioner, wiping with a soft cloth.

Take care not to extend the area of contamination beyond its original boundary. Rinse with clean water.

Our vinyls should be periodically cleaned to maintain their appearance and prevent build-up of dirt and contaminants. Any stain, spill or soiling should be cleaned up promptly to prevent permanent staining. When cleaning, always rub gently.

Caution: Powdered abrasives, abrasive cleaners, and steel wool damage vinyl, as do strong solvents, lacquer solvents and inks. Lotions, suntan oil, waxes and polishes, etc., oils and dyes that can cause stiffening and staining of vinyls. Never use heat guns or hair dryers.

Note: Stronger cleaners, detergents, and solvents may be effective in stain removal but can cause either immediate damage or slow deterioration. Many such materials are wrongly recommended in marine and other related industries. The use of such cleaners is at the owner's own risk.

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing, but it is not intended to relieve the user from their responsibility to investigate and understand other pertinent sources of information and to comply with the laws and procedures applicable to the safe handling and use of this material.



Morbern
Corporate Headquarters
 80 Boundary Road
 Cornwall, ON K6H-6M1
 Canada
 Phone: 613.932.8811
888-MORBERN

Morbern
US Headquarters
 401 Fraley Road
 High Point, NC 27263
 United States
888-MORBERN

Morbern is a premier North American manufacturer and innovator of decorative vinyl-coated fabrics. With a legacy spanning over half a century, we are dedicated to providing leading-edge design and engineered performance solutions in upholstery for sectors in Marine, Automotive, Recreational Vehicles, Mass Transportation, Corporate, Healthcare, Hospitality, and other diverse seating markets.

