

Specifications

- → Roll Width: 54 inches
- → Roll Length: 40 yards
- → Weight: 29.25 ± 2 oz per linear yard
- → Thickness: 45 ± 5 mils
- → Cold Crack: -25°F

Abrasion Resistance

No Significant wear after 200,000 double rubs with #10 cotton duck using the Wyzenbeek test method.

Feature and Benefits

Mildew resistant, Made in North America, Bromine-free, No halogenated flame, Retardants (HFRs), REACH compliant, RoHS compliant, Non toxic, No heavy metals, No mercury, No bisphenol A (BPA), No ozone depleting chemicals, No PBT's (persistent bio accumulative and toxic chemicals), Contains bio-based renewable ingredients, Formulated without ortho-phthalates, 650 Hours QUV

Flame Resistance

Manufactured to meet the following flammability* requirements:

- → CA TB 117-2013 (Section 1 - Cover Fabric)
- → UFAC Class 1
- → NFP 260
- → FMVSS 302

*This term and corresponding data refer to the typical performance in the specific testindicated. They should not be construed to imply the behaviour of this or any other material under actual fire conditions.

Content and Backing

Vinyl, Backing: 100% Polyester Mellohide

Recommended Applications

Automotive, Hospitality, General Upholstery, Residential/Home Office, Hotel/Motel, Restaurant, RV, Workstations, Corporate

*The specifier must comply with all applicable building codes, as well as state and federal regulations.

Care and Cleaning Instructions

To prevent build up of dirt and contaminates, which may cause permanent staining, periodic cleaning is highly suggested. The frequency of cleaning is dependent upon the environmental conditions the material is subjected to.

For normal cleaning: Most stains can be easily cleaned using warm, soapy water and clear water rinses. Moderate scrubbing with a medium bristle brush will help loosen soiling materials from the depressions of embossed surfaces. For more stubborn stains, use Formula 409® commercially available cleaner in accordance with the manufacturer's instructions. Full strength rubbing alcohol or mineral spirits* may be tried cautiously as a last resort on very stubborn stain, if the above suggestions do not work. Indiscriminate use of any solvent, or solvent containing cleaner, can severely damage or discolor vinyl. Always follow with a clear water rinse after cleaning with solvents.

Note: Detergents should never be used on a regular or repeated basis for normal cleaning. Morbern recommends repeated rinsing with clear water after any cleaning procedure. When opening a new container, please test the cleaner in an inconspicuous area as cleaning manufacturers may change formula without notice. Morbern cannot be responsible when unknown changes are made by the manufacturer of the cleaner to their formulations between our 6-month verification intervals.

*Caution: Exercise care as these solvents are flammable.
Use only small quantities of solvents and keep clear of any sources of ignition. Wear protective gloves and ensure cleaning takes place in a well ventilated area.




Morbern Corporate Headquarters 80 Boundary Road Cornwall, ON K6H-6M1 Canada 888-MORBERN

Morbern
US Headquarters
401 Fraley Road
High Point, NC 27263
United States
888-MORBERN

Morbern is a premier North American manufacturer and innovator of decorative vinyl-coated fabrics. With a legacy spanning over half a century, we are dedicated to providing leading-edge design and engineered performance solutions in upholstery for sectors in Marine, Automotive, Recreational Vehicles, Mass Transportation, Corporate, Healthcare, Hospitality, and other diverse seating markets.

© 2025 Morbern™ | Morbern is an ISO 14001 : 2015 Certified Producer





ALLANTE