



ALLANTITE FREE

Specifications

- Roll Width: 54 inches
- Roll Length: 40 yards
- Weight: 29.3 ± 2 oz per linear yard
- Thickness: 45 ± 5 mils
- Cold Crack: -25°F
- 150 hours QUV

Abrasion Resistance

Wyzenbeek test method: #10 Cotton Duck;
250,000 Cycles Pass: No significant wear.

Feature and Benefits

Flame Retardant Additive Free, ANti-Microbial Retardant Additive Free, Formulated Phthalate Free, Denim Dye Resistant, Oil Resistant, Cleanable, Made in North America, Bromin-free, No Halogenated Flame Retardants (HFRs), REACH Compliant, RoHS Compliant, No Heavy Metals, No Mercury, No Bisphenol A (BPA) No Ozone Depleting Chemicals, No PBT's (Persistent Bio-Accumulative Toxic Chemicals, Contains Bio-Based Renewable Ingredients.

Flame Resistance

Manufactured to meet the following flammability* requirements:

- EN 1021-1 and 2
- Cal TB 117-2013 (Section 1-Cover Fabric)
- UFAC Class 1
- AB2998, NY SB S4630B
- Compliance NFP 260

*This term and corresponding data refer to the typical performance in the specific test indicated. They should not be construed to imply the behaviour of this or any other material under actual fire conditions.

Content and Backing

Vinyl, Backing: 100% Polyester Mellohide

Recommended Applications

Contract, Public Spaces, Hotel/Motel/Entertainment, Restaurant, General Upholstery, Residential/Home Office, RV, Casino, Marine Interior

Care and Cleaning Instructions

This product has been developed to emulate the look and feel of soft leather. The unique super dull finish is designed to be low burnishing, non-polishing and resistant to ultraviolet exposure.

Our vinyls have superb tailoring qualities, which make pre-heating and steaming unnecessary and are not recommended in the fabrication process.

Because of the special leather-like finish, additional precautions should be observed when processing and cleaning. Please avoid contact with marking inks, glues and other staining materials that may damage vinyl during manufacturing. Protecting seating with a clean polyethylene cover, as is common in the automotive industry, should enable you to deliver a stain-free unit to the customer.

If, despite all precautions, staining material does come in contact with our vinyls, cleaning should be immediate and should follow these instructions:

- Dry soil, Dust and Dirt, Dried on Dirt: Remove with soft cloth dampened with water.
- Variation in Surface Gloss: Wipe with a soft cloth dampened with water. Allow to air dry.
- Stubborn Dirt: Wash with a soft cloth moistened with a mild soap and water. Rinse with clean water.
- Stubborn Spots and Stains: Spray with either Formula 409®, or CRC 40173 Tannery Leather, Vinyl & More Cleaner & Conditioner, wiping with a soft cloth. Rinse with clean water.
- Liquid Spills: Wipe immediately with a clean absorbent cloth. Rinse with clean water.
- Food, Grease, and Oily Stains: Spray immediately using either Formula 409® or CRC 40173 Tannery Leather, Vinyl & More Cleaner & Conditioner, wiping with a soft cloth.

Take care not to extend the area of contamination beyond its original boundary. Rinse with clean water.

Our vinyls should be periodically cleaned to maintain their appearance and prevent build-up of dirt and contaminants. Any stain, spill or soiling should be cleaned up promptly to prevent permanent staining. When cleaning, always rub gently.

Caution: Powdered abrasives, abrasive cleaners, and steel wool damage vinyl, as do strong solvents, lacquer solvents and inks. Lotions, suntan oil, waxes and polishes, etc., oils and dyes that can cause stiffening and staining of vinyls. Never use heat guns or hair dryers.

Note: Stronger cleaners, detergents, and solvents may be effective in stain removal but can cause either immediate damage or slow deterioration. Many such materials are wrongly recommended in marine and other related industries. The use of such cleaners is at the owner's own risk.

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing, but it is not intended to relieve the user from their responsibility to investigate and understand other pertinent sources of information and to comply with the laws and procedures applicable to the safe handling and use of this material.





ALLANTTE FREE



AF-901
Bright White



AF-917
White Crush



AF-922
Ivory



AF-910
Illusion




AF-907
Bleached Sand




AF-911
Taupe Fawn




AF-939
Birch




AF-938
Mist




AF-913
Warm Smoke




AF-915
Cookie




AF-904
Garden Green



AF-937
Golden Kiwi



AF-912
Sierra Brick




AF-941
Desert Sun




AF-942
Ginger Spice




AF-945
Flannel




AF-940
Blooming Dahlia



AF-925
Italian Rose




AF-916
Red Truffle



AF-944
Thais Red




AF-905
Province Blue




AF-909
Autumn Rain




AF-902
Ice




AF-933
Mystic Lilly




AF-934
Winter Green



AF-914
Oasis Green



AF-928
Horizon



AF-931
Hawaiian Surf




AF-929
Nautical Blue




AF-923
Mountain Sky




AF-946
Elephant




AF-926
Niagara Mist




AF-930
Regatta



AF-936
Lagoon




AF-935
Pagoda



AF-927
Riverside



AF-908
Old Navy




AF-920
Galaxy




AF-924
Purple Impulse




AF-932
Malibu Blue




AF-903
Gibraltar




AF-943
Granite




AF-906
Chateau Grey



AF-921
Chocolate Sundae



AF-919
Eclipse



AF-918
Ink Black