



SANIBEL




SAN-110
Sharkskin




SAN-120
Sea Chalk




SAN-112
Seaform White




SAN-121
Cream




SAN-122
Bisque




SAN-136
White




SAN-138
Off White



SAN-116
Glacier



SAN-111
Moon



SAN-103
Sunset




SAN-146
Sunrise




SAN-118
Teal




SAN-140
Ocean Blue




SAN-103
Coffee




SAN-130
Charcoal



SAN-115
Blue



SAN-108
Atlantic



SAN-102
Storm

Specifications

- Roll Width: 54 inches
- Roll Length: 30 yards
- Weight: 32 +/- 2 oz per linear yard
- Thickness: 39 +/- 4 mils
- ColdCrack: -25°F

Abrasion Resistance

No significant wear after 30,000 double rubs with #10 cotton duck using the Wyzenbeek method.

Feature and Benefits

Mildew resistant, Bromine-free, No halogenated flame, Retardants (HFRs), REACH compliant, RoHS compliant, Non toxic, No heavy metals, No bisphenol A (BPA), No ozone depleting chemicals, No PBT's (persistent bio accumulative and toxic chemicals), Contains bio-based renewable ingredients

Flame Resistance

Manufactured to meet the following flammability* requirements:

- FMVSS-302
- Cal TB 117-2013 (Section 1-Cover Fabric)
- NFPA 260
- UFAC Class 1
- IMO MSC 88/26/ADD. 2 PART 8 (3.1 and 3.2)

* This term and corresponding data refer to the typical performance in the specific test indicated. They should not be construed to imply the behaviour of this or any other material under actual fire conditions.

Content and Backing

Vinyl, Backing: 100% Polyester Mellohide

Recommended Applications

General Upholstery, Auto/Marine Aftermarket, Recreational Products, Marine Exterior, Marine Interior

*The specifier must comply with all applicable building codes, as well as state and federal regulations

Care and Cleaning Instructions

To prevent build up of dirt and contaminants, which may cause permanent staining, periodic cleaning is highly suggested. The frequency of cleaning is dependent upon the environmental conditions the material is subjected to.

For normal cleaning: Most stains can be easily cleaned using warm, soapy water and clear water rinses. Moderate scrubbing with a medium bristle brush will help loosen soiling materials from the depressions of embossed surfaces.

For more stubborn stains, use Formula 409® commercially available cleaner in accordance with the manufacturer's instructions. Full strength rubbing alcohol or mineral spirits* may be tried cautiously as a last resort on very stubborn stain, if the above suggestions do not work. Indiscriminate use of any solvent, or solvent containing cleaner, can severely damage or discolor vinyl. Always follow with a clear water rinse after cleaning with solvents.

Note: Detergents should never be used on a regular or repeated basis for normal cleaning. Morbern recommends repeated rinsing with clear water after any cleaning procedure. When opening a new container, please test the cleaner in an inconspicuous area as cleaning manufacturers may change formula without notice. Morbern cannot be responsible when unknown changes are made by the manufacturer of the cleaner to their formulations between our 6-month verification intervals.

* Caution: Exercise care as these solvents are flammable.

Use only small quantities of solvents and keep clear of any sources of ignition. Wear protective gloves and ensure cleaning takes place in a well ventilated area.



Morbern
Corporate Headquarters
80 Boundary Road
Cornwall, ON K6H-6M1
Canada
888-MORBERN

Morbern
US Headquarters
401 Fraley Road
High Point, NC 27263
United States
888-MORBERN

Morbern is a premier North American manufacturer and innovator of decorative vinyl-coated fabrics. With a legacy spanning over half a century, we are dedicated to providing leading-edge design and engineered performance solutions in upholstery for sectors in Marine, Automotive, Recreational Vehicles, Mass Transportation, Corporate, Healthcare, Hospitality, and other diverse seating markets.